

# HYDRAULIC COMPRESSION HEAD



## Model No. **EP-60D 60Ton output compression head**



EP-60D Compression Head



HPE-3 Recommended hydraulic pump

### **SPECIFICATIONS**

Ram stroke: 38.5mm  
between dies.

Oil volume required:  
303cc

Force at die face: 517kN

### **SIZE**

260mm Dia. x 446 (H)  
mm

### **WEIGHT**

23.0 kg

### **ACCESSORIES**

Steel Carrying case

Ground Stand

### **REMARKS**

Dies are sold separately.

Light Weight

Removable die cap for easy  
connector positioning.

Simple compact design for  
easy maintenance.

Double acting hydraulics for  
quick and easy compressions.

HPE-3 Engine driven  
hydraulic pump is  
recommended for use with  
this compression head.

### **FEATURES**

The EP-60D is a 60ton  
output compression head  
for full tension ,  
transmission line  
connectors and requires  
and external double  
acting 700bar pumping  
source.

Double acting means  
hydraulically advancing  
the ram to build the  
tonnage, then hydraulic  
pressure is reversed to  
retract the ram. This will  
expedite the compression  
cycle time

Please specify the dia. of  
the manufacturers  
connectors or Alcan die  
no. ie A-9, A-10 etc, with  
order.