

Model No. **PB-10N Hydraulic Pipe Bender**



PB-10N Pipe Bender

R14EFL Motor driven hydraulic pump suitable for PB-10N

SPECIFICATIONS

Ram stroke: 250mm
Oil volume required:
400cc
Output Force:108kN

SIZE

780mm (W)

WEIGHT

18.6kg

ACCESSORIES

Frame, Cylinder,
Pivot Shoes (2 Pieces)
Angle gauge

REMARKS

Hydraulic pump and bending shoes sold separately.

Bending Shoe Sizes:

Thin Conduit (A)
Thick Conduit (B)
Gas Pipe (SGP)

	Size Pipe Dia.	Size Pipe Dia.		
	A15 15.9	B42 47.8		
	A19 19.1	B54 59.6		
	A25 25.4	B70 75.2		
	A31 31.8	B82 87.9		
	A39 38.1	SGP-15 21.7		
	A51 50.8	SGP-20 27.2		
	A63 63.5	SGP-25 34.0		
	A75 76.2	SGP-32 42.7		
	B16 21.0	SGP-40 48.6		
	B22 26.5	SGP-50 60.5		
	B28 33.3	SGP-65 76.3		
	B36 41.9			

FEATURES

The PB-10N was designed to bend various sizes and thickness of Steel pipes without wrinkles.

An aluminium alloy frame makes this bender lighter so that it can be easily carried to site.

Bending shoes are designed to bend JIS standard conduit pipe and gas pipe listed on the chart adjacent. If the pipe outer diameter being bent is equivalent to the one from the chart, the shoe can be used for that application.

Requires a separate hydraulic pump similar to the one shown above.